

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 1 130 913 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
05.09.2001 Bulletin 2001/36

(51) Int Cl.7: H04N 5/765

(21) Application number: 01104257.9

(22) Date of filing: 22.02.2001

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: Hajime, Hata, c/o Sony Corporation
Shinagawa-ku, Tokyo (JP)

(74) Representative: Körber, Martin, Dipl.-Phys. et al
Mitscherlich & Partner,
Patent- und Rechtsanwälte,
Postfach 33 06 09
80066 München (DE)

(30) Priority: 24.02.2000 JP 2000047558


(71) Applicant: SONY CORPORATION
Tokyo (JP)

(54) Image capturing apparatus and method, and recording medium therefor

(57) In order that a digital video (DV) camera function as a WWW server in a network, an image capturing section (11) captures an image of a subject. A DV encoder (12) encodes an image signal input from the image capturing section (11). A recording and playback section (14) plays back DV data recorded in a DV cassette tape (15). An IP packet assembling/disassembling section (19) assembles a DV signal input from the DV

encoder (12), a DV signal input from the recording and playback section (14), or an HTML file input from a WWW server processing section (21) into IP packets, and outputs them to an IEEE 1394 interface (20). The IEEE 1394 interface (20) transmits, via the network (2), the IP packets input from the IP packet assembling/disassembling section (19) to a personal computer which accessed the DV camera.

FIG. 2



Description

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0001] The present invention relates to an image capturing apparatus, an image capturing method, and a recording medium therefor. More particularly, the present invention relates to an image capturing apparatus and an image capturing method, which are suitable for use in a case where moving image data for which streaming playback is possible is to be transmitted via the Internet, and to a recording medium therefor.

2. Description of the Related Art

[0002] Conventionally, in order to convert moving images captured using a digital video camera (hereinafter referred to as a "DV camera") into data for which streaming playback is possible, which is made public in a home page, etc., opened in the Internet, it is necessary to take a moving image (DV data) captured using a DV camera into, for example, a personal computer via an IEEE 1394 bus, whereby the data is converted into a predetermined data format in which streaming playback is possible.

[0003] In order to convert the DV data which is taken into a personal computer into a predetermined data format in which streaming playback is possible, there is a problem in that appropriate operations must be performed for a dedicated application program, and operations thereof are difficult.

[0004] Furthermore, in order to make public the moving image data converted into a predetermined data format in a home page, there is a problem in that regarding the moving image data, a WWW (World Wide Web) server for managing HTML (Hyper Text Markup Language) files, etc., of the home page must be provided in the Internet.

SUMMARY OF THE INVENTION

[0005] The present invention has been achieved in view of such circumstances. An object of the present invention is to make it possible for the DV camera to function as a WWW server in the Internet.

[0006] To achieve the above-mentioned object, according to a first aspect of the present invention, there is provided an image capturing apparatus which can be connected to a network, comprising: image capturing means for capturing a moving image; storage means for storing the moving image captured by the image capturing means; playback means for playing back the moving image stored by the storage means; maintaining means for maintaining an HTML file which forms a predetermined screen; receiving means for receiving a command output by another electronic device via the network; transmission means for transmitting the HTML

file maintained by the maintaining means to the other electronic device via the network in such a manner as to correspond to the command received by the receiving means; coding means for coding the moving image captured by the image capturing means or the moving image played back by the playback means by a predetermined method and for generating coded data; and supply means for supplying the coded data generated by the coding means to the other electronic device via the network in such a manner as to correspond to the command received by the receiving means.

[0007] The image capturing apparatus may further comprise checking means for checking the status of the network; and coding-rate control means for controlling the coding rate of the coding means in such a manner as to correspond to the checked result of the checking means.

[0008] The image capturing apparatus may further comprise playback speed control means for controlling the playback speed of the playback means in such a manner as to correspond to the checked result of the checking means.

[0009] According to a second aspect of the present invention, there is provided an image capturing method comprising: an image capturing step of capturing a moving image; a storing step of storing the moving image captured in the image capturing step; a playback step of playing back the moving image stored in the storing step; a maintaining step of maintaining an HTML file which forms a predetermined screen; a receiving step of receiving a command output by another electronic device via the network; a transmission step of transmitting the HTML file maintained in the maintaining step to the other electronic device via the network in such a manner as to correspond to the command received in the receiving step; a coding step of coding the moving image captured in the image capturing step or the moving image played back in the playback step by a predetermined method and for generating coded data; and a supplying step of supplying the coded data generated in the coding step to the other electronic device via the network in such a manner as to correspond to the command received in the receiving step.

[0010] According to a third aspect of the present invention, there is provided a recording medium having recorded therein a computer-readable program, the program comprising: an image capturing step of capturing a moving image; a storing step of storing the moving image captured in the image capturing step; a playback step of playing back the moving image stored in the storing step; a maintaining step of maintaining an HTML file which forms a predetermined screen; a receiving step of receiving a command output by another electronic device via the network; a transmission step of transmitting the HTML file maintained in the maintaining step to the other electronic device via the network in such a manner as to correspond to the command received in the receiving step; a coding step of coding the moving image cap-

tured in the image capturing step or the moving image played back in the playback step by a predetermined method and of generating coded data; and a supplying step of supplying the coded data generated in the coding step to the other electronic device via the network in such a manner as to correspond to the command received in the receiving step.

[0011] In the image capturing apparatus, the image capturing method, and the program in the recording medium in accordance with the present invention, a moving image is captured, the captured moving image is stored, and the stored moving image is played back. Furthermore, an HTML file which forms a predetermined screen is maintained, a command which is output by another electronic device is received via a network, and the maintained HTML file is transmitted to the other electronic device via the network in such a manner as to correspond to the received command. In addition, coded data in which the captured moving image or the played-back moving image is coded by a predetermined method is generated, and the generated coded data is supplied to the other electronic device via the network in such a manner as to correspond to the received command.

[0012] The above and further objects, aspects and novel features of the invention will become more fully apparent from the following detailed description when read in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0013]

Fig. 1 is a diagram illustrating a DV camera 1 according to the present invention;
 Fig. 2 is a block diagram showing a first example of the construction of the DV camera 1;
 Fig. 3 is a flowchart illustrating the operation of the first example of the construction of the DV camera 1;
 Fig. 4 is a block diagram showing a second example of the construction of the DV camera 1;
 Fig. 5 is a block diagram showing the operation of the second example of the construction of the DV camera 1;
 Fig. 6 is a block diagram showing a third example of the construction of the DV camera 1;
 Fig. 7 is a diagram showing an example of a display of an HTML file output by the DV camera 1; and
 Figs. 8A, 8B, and 8C are diagrams illustrating media which are used to install a program into a computer so as to be placed in an executable state.

DESCRIPTION OF THE PREFERRED EMBODIMENT

[0014] A DV camera 1 according to the present invention is connected to personal computers 3-1 to 3-3 (hereinafter referred to simply as a "personal computer

3" when there is no need to distinguish the personal computers 3-1 to 3-3 individually) via a network 2 typified by the Internet, as shown in Fig. 1. The DV camera 1 records a captured moving image and plays it back, and further functions as a WWW server. In the personal computer 3, a WWW browser program recorded in a built-in hard disk, etc., is loaded into a RAM, and the program is executed by a CPU. As a result, the personal computer 3 accesses the DV camera 1 as a WWW server, obtains an HTML file, and displays the image of the corresponding home page on a display.

[0015] Fig. 2 shows a first example of the construction of the DV camera 1. An image capturing section 11 captures an image of a subject, converts the light information of the moving image into an electrical signal (moving image signal), and outputs it to a DV encoder 12 and an NTSC conversion section 17. A DV encoder 12 encodes the moving image signal input from the image capturing section 11 into a DV format, and outputs the obtained DV signal to a recording and playback section 14 and an IP packet assembling/disassembling section 19. A control section 13 controls the entirety of the DV camera 1 in accordance with an operation command input from a user or a WWW server processing section 21. The recording and playback section 14 records DV data input from the DV encoder 12 in a DV cassette tape 15. The recording and playback section 14 further plays back the DV data recorded in the DV cassette tape 15 and outputs it to a DV decoder 16 and the IP packet assembling/disassembling section 19.

[0016] The DV decoder 16 decodes the DV data input from the recording and playback section 14 and outputs the obtained image signal to the NTSC conversion section 17. The NTSC conversion section 17 converts the image signal input from the image capturing section 11 or the DV decoder 16 into an NTSC signal and outputs it to a liquid-crystal display (LCD) 18. The liquid-crystal display 18 displays an image corresponding to the NTSC signal input from the NTSC conversion section 17.

[0017] The IP packet assembling/disassembling section 19 assembles a DV signal input from the DV encoder 12, a DV signal input from the recording and playback section 14, or an HTML file input from the WWW server processing section 21 into IP packets, and outputs them to an IEEE 1394 interface (I/F) 20. The IP packet assembling/disassembling section 19 further separates a command, such as an access request, from the IP packets input from the IEEE 1394 interface 20 and outputs it to the WWW server processing section 21. The IEEE 1394 interface 20 transmits the IP packets input from the IP packet assembling/disassembling section 19 to the personal computer 3 which accessed the DV camera 1 via the network 2. The IEEE 1394 interface 20 further receives a command, such as an access request, which was transmitted by the personal computer 3, and outputs it to the IP packet assembling/disassembling section 19 via the network 2.

[0018] The WWW server processing section 21 reads

an HTML file from a storage section 22 and outputs it to the IP packet assembling/disassembling section 19 in such a manner as to correspond to the command input from the IP packet assembling/disassembling section 19. The WWW server processing section 21 further outputs an operation command corresponding to the command input from the IP packet assembling/disassembling section 19 to the control section 13. The storage section 22 stores an HTML file which forms a home page. In the home page, a display informing that streaming playback of a real-time moving image or a recorded moving image is possible, and a button for instructing the start of the processing are displayed.

[0019] Next, the operation of a first example of the construction of the DV camera 1 shown in Fig. 2 is described with reference to the flowchart in Fig. 3. In step S1, when an access to the DV camera 1 is made from the WWW browser activated in the personal computer 3 via the network 2 (when a transmission of an HTML file of the home page is requested), IP packets containing the access command are received by the IEEE 1394 interface 20 of the DV camera 1 and are supplied to the IP packet assembling/disassembling section 19.

[0020] In step S2, the IP packet assembling/disassembling section 19 separates an access command from the IP packets input from the IEEE 1394 interface 20 and outputs it to the WWW server processing section 21. The WWW server processing section 21 reads the HTML file from the storage section 22 in such a manner as to correspond to the access command input from the IP packet assembling/disassembling section 19 and outputs it to the IP packet assembling/disassembling section 19. The IP packet assembling/disassembling section 19 assembles the HTML file input from the WWW server processing section 21 into IP packets and outputs them to the IEEE 1394 interface 20. The IEEE 1394 interface 20 transmits the IP packets of the HTML file input from the IP packet assembling/disassembling section 19 to the corresponding personal computer 3 via the network 2.

[0021] In the personal computer 3, the WWW browser causes the home page corresponding to the HTML file to be displayed on a display, prompting the user to instruct the starting of the stream playback of the moving image. When, in response to this display, the user of the personal computer 3 depresses the button for instructing the starting of the streaming playback of a real-time moving image or a recorded moving image, which is displayed in the home page, the transmission request of the moving image data is transmitted from the WWW browser to the WWW server processing section 21 of the DV camera 1 via the network 2.

[0022] In step S3, the WWW server processing section 21 determines whether or not a request of transmitting the moving image data has been made from the personal computer 3 which is making access, and waits until it is determined that a request for transmitting the moving image data is made. Then, when it is determined

that a request for transmitting moving image data is made, the process proceeds to step S4. In step S4, the WWW server processing section 21 determines whether the moving image data for which transmission has been requested is real-time moving image data or recorded moving image data, and outputs the determination result to the control section 13.

[0023] When it is determined in step S4 that the moving image data for which transmission has been requested is real-time moving image data, the process proceeds to step S5. In step S5, the image capturing section 11 starts to capture an image under the control of the control section 13, and outputs the obtained moving image signal to the DV encoder 12. In step S6, the DV encoder 12 encodes the input image signal input from the image capturing section 11 into a DV format, and outputs the obtained DV signal to the IP packet assembling/disassembling section 19.

[0024] In step S7, the IP packet assembling/disassembling section 19 assembles the DV signal input from the upper stage into IP packets and outputs them to the IEEE 1394 interface 20. In step S8, the IEEE 1394 interface 20 transmits the IP packets input from the IP packet assembling/disassembling section 19 to the corresponding personal computer 3 via the network 2. The moving image data supplied to the personal computer 3 is decoded by, for example, a predetermined plug-in application of the WWW browser, and the data is displayed in a moving-image display area 51 (see Fig. 7) in the home page.

[0025] When it is determined in step S4 that the moving image data for which transmission has been requested is recorded moving image data, the process proceeds to step S9. In step S9, the recording and playback section 14 plays back the DV data recorded in the DV cassette tape 15 and outputs it to the IP packet assembling/disassembling section 19 under the control of the control section 13.

[0026] As a result of performing such server processing as that described above, it becomes possible to supply moving image data which has been captured by the DV camera 1 or moving image data recorded in the DV cassette tape 15 to the personal computer 3 via the network 2.

[0027] Next, Fig. 4 shows a second example of the construction of the DV camera 1. This second example of the construction is such that a line checking section 31 and a format-rate conversion section 32 are added to the first example of the construction shown in Fig. 2. The line checking section 31 checks the communication capacity and the degree of congestion of the network 2 via the IEEE 1394 interface 20, and outputs the results to the format-rate conversion section 32. The format-rate conversion section 32 determines the compression rate of the image data on the basis of the capacity, etc., of the line, which is input from the line checking section 31, codes the image data input from the image capturing section 11 or the DV decoder 16 by, for example, a cod-

ing method (for example, an MPEG-2 (Moving Picture Experts Group-2) method, a Real Video (trademark) method, etc.) in which the compression rate can be changed and streaming playback is possible, and outputs the data to the IP packet assembling/disassembling section 19.

[0028] The operation of the second example of the construction of the DV camera 1 shown in Fig. 4 will now be described with reference to the flowchart in Fig. 5. In step S11, when an access to the DV camera 1 is made from the WWW browser activated in the personal computer 3 via the network 2 (when a transmission of an HTML file of the home page is requested), the IP packets containing the access command are received by the IEEE 1394 interface 20 of the DV camera 1 and are supplied to the IP packet assembling/disassembling section 19.

[0029] In step S12, the IP packet assembling/disassembling section 19 separates the access command from the IP packets input from the IEEE 1394 interface 20 and outputs it to the WWW server processing section 21. The WWW server processing section 21 reads an HTML file from the storage section 22 in such a manner as to correspond to the access command input from the IP packet assembling/disassembling section 19, and outputs the HTML file to the IP packet assembling/disassembling section 19. The IP packet assembling/disassembling section 19 assembles the HTML file input from the WWW server processing section 21 into IP packets, and outputs them to the IEEE 1394 interface 20. The IEEE 1394 interface 20 transmits the IP packets of the HTML file, input from the IP packet assembling/disassembling section 19, to the corresponding personal computer 3 via the network 2.

[0030] In the personal computer 3, the WWW browser causes a corresponding home page of the HTML file to be displayed, prompting the user to instruct the starting of the stream playback of the moving image. When, in response to this prompt, the user of the personal computer 3 depresses the button for instructing the starting of the stream playback of a real-time moving image or a recorded moving image, which is displayed in the home page, the transmission request of the moving image data is transmitted from the WWW browser to the WWW server processing section 21 of the DV camera 1 via the network 2.

[0031] In step S13, the WWW server processing section 21 determines whether or not a request of transmitting the moving image data has been made from the personal computer 3 which is making access, and waits until it is determined that the request for transmitting moving image data is made. Then, when it is determined that the request for transmitting the moving image data is made, the process proceeds to step S14. In step S14, the WWW server processing section 21 determines whether the moving image data for which transmission has been requested is real-time moving image data or recorded moving image data, and outputs the determi-

nation result to the control section 13.

[0032] When it is determined in step S14 that the moving image data for which transmission has been requested is real-time moving image data, the process proceeds to step S15. In step S15, the image capturing section 11 starts to capture an image under the control of the control section 13, and outputs the obtained moving image signal to the format-rate conversion section 32.

[0033] In step S16, the line checking section 31 checks the communication capacity and the degree of congestion of the network 2 via the IEEE 1394 interface 20, and outputs the results to the format-rate conversion section 32. In step S17, the format-rate conversion section 32 determines the compression rate of the image data on the basis of the capacity, etc., of the line, which is input from the line checking section 31, codes the image data input from the upper stage by a predetermined coding method by using the compression rate, and outputs it to the IP packet assembling/disassembling section 19.

[0034] In step S18, the IP packet assembling/disassembling section 19 assembles the coded moving image data, which is input from the format-rate conversion section 32, into IP packets, and outputs them to the IEEE 1394 interface 20. In step S19, the IEEE 1394 interface 20 transmits the IP packets input from the IP packet assembling/disassembling section 19 to the corresponding personal computer 3 via the network 2. The moving image data supplied to the personal computer 3 is decoded by, for example, a predetermined plug-in application of the WWW browser, and the data is displayed in the moving-image display area 51 in the home page.

[0035] If it is determined in step S14 that the moving image data for which transmission has been requested is recorded moving image data, the process proceeds to step S20. In step S20, the recording and playback section 14 plays back the DV data recorded in the DV cassette tape 15 and outputs it to the DV decoder 16 under the control from the control section 13. In step S21, the DV decoder 16 decodes the DV signal input from the recording and playback section 14 and outputs the obtained moving image data to the format-rate conversion section 32.

[0036] As a result of performing such server processing as that described above, it becomes possible to supply the moving image data to the personal computer 3 in such a manner as to correspond to the status of the network 2, such as, for example, the compression rate being increased to decrease the rate of codes to be communicated when the communication capacity is small or when the line is congested, or the compression rate being decreased to improve the quality of a moving image when the communication capacity is large or the line is free.

[0037] Next, Fig. 6 shows a third example of the construction of the DV camera 1. This third example of the

construction is such that a line checking section 41 is added to the first example of the construction shown in Fig. 2. The line checking section 41 checks the communication capacity and the degree of congestion of the network 2 via the IEEE 1394 interface 20 as necessary, and outputs the results to the control section 13. The control section 13 controls mainly the recording and playback section 14 in order to adjust the playback speed of the DV cassette tape 15 on the basis of the capacity, etc., of the line, which is input from the line checking section 41.

[0038] According to the third example of the construction of the DV camera 1, for example, when the communication capacity of the network 2 is small or when the line is congested, in the recording and playback section 14, the playback speed of the DV cassette tape 15 is delayed so that the transfer speed of the DV data to the IP packet assembling/disassembling section 19 is decreased. As a consequence of this, since the transfer rate is decreased also in each section after the IP packet assembling/disassembling section 19, it becomes possible to communicate the moving image data at an appropriate transfer rate in the network 2.

[0039] Fig. 7 shows an example of a display in which the HTML file of the home page and the moving image data, supplied from the DV camera 1 to the personal computer 3 via the network, are processed by a WWW browser activated in the personal computer 3 and the plug-in application thereof, and they are displayed on a display. As shown in Fig. 7, in the window of the WWW browser, a moving-image display area 51 is provided, and a moving image is displayed therein. As shown in Fig. 7, on the screen of the home page, an operation button 52 for instructing a command (zooming, playback, rewinding, fast forwarding, time set recording, etc.) for the DV camera 1 may be provided so that the DV camera 1 which is connected via the network 2 can be controlled from the screen of the personal computer 3 in response to a click, etc., on the operation button 52.

[0040] Although the above-described series of processing can be performed by hardware, it can also be performed by software. In a case where the series of processing is to be performed by software, programs which form the software are installed into a computer incorporated into the DV camera 1 as dedicated hardware or are installed into, for example, a general-purpose personal computer capable of executing various types of functions as a result of various programs being installed.

[0041] Next, referring to Figs. 8A to 8C, a description is given of media which are used to install a program for executing the above-described series of processing into a computer so as to be placed in a computer-executable state.

[0042] The program, as shown in Fig. 8A, may be provided to the user in a state in which the program is installed in advance in a hard disk 102 as a recording medium contained in a computer 101 or in a semiconductor

memory 103.

[0043] Alternatively, the program, as shown in Fig. 8B, may be stored temporarily or permanently in a recording medium, such as a floppy disk 111, a CD-ROM (Compact Disc-Read Only Memory) 112, an MO (Magnetooptical) disk 113, a DVD (Digital Versatile Disc) 114, a magnetic disk 115, or a semiconductor memory 116, and may be provided as package software.

[0044] In addition, the program, as shown in Fig. 8C, may be transferred from a download site 121 to a computer 123 by wireless via a satellite 122, or may be transferred to the computer 123 by cables or by wireless via a network 131 such as a local area network or the Internet, and in the computer 123, the program may be stored in the hard disk contained therein.

[0045] The "media" in this specification indicates the concept in the broad sense, containing all these media.

[0046] In this specification, steps which describe a program provided by a medium contain not only processing performed in a time-series manner along the described sequence, but also processing performed in parallel or individually although the processing is not necessarily performed in a time-series manner.

[0047] In this specification, the "system" represents the overall apparatus composed of plural devices.

[0048] As has thus been described, according to the image capturing apparatus, the image capturing method, and the program in the recording medium in accordance with the present invention, a captured moving image or a played-back moving image is coded by a predetermined method in order to generate coded data, and the generated coded data is supplied to another electronic device via a network in such a manner as to correspond to a received command. Thus, it becomes possible for the DV camera to function as a WWW server in the network.

[0049] Many different embodiments of the present invention may be constructed without departing from the spirit and scope of the present invention. It should be understood that the present invention is not limited to the specific embodiment described in this specification. To the contrary, the present invention is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the invention as hereafter Claimed. The scope of the following Claims is to be accorded the broadest interpretation so as to encompass all such modifications, equivalent structures and functions.

Claims

1. An image capturing apparatus which can be connected to a network, comprising:

image capturing means for capturing a moving image;

storage means for storing said moving image

captured by said image capturing means;
 playback means for playing back said moving
 image stored by said storage means;
 maintaining means for maintaining an HTML
 file which forms a predetermined screen; 5
 receiving means for receiving a command out-
 put by another electronic device via said net-
 work;
 transmission means for transmitting said HTML
 file maintained by said maintaining means to 10
 said other electronic device via said network in
 such a manner as to correspond to said com-
 mand received by said receiving means;
 coding means for coding said moving image 15
 captured by said image capturing means or
 said moving image played back by said play-
 back means by a predetermined method and
 for generating coded data; and
 supply means for supplying said coded data 20
 generated by said coding means to said other
 electronic device via said network in such a
 manner as to correspond to said command re-
 ceived by said receiving means.

2. An image capturing apparatus according to Claim 25
 1, further comprising:

checking means for checking the status of said
 network; and
 coding-rate control means for controlling the 30
 coding rate of said coding means in such a
 manner as to correspond to the checked result
 of said checking means.

3. An image capturing apparatus according to Claim 35
 2, further comprising:

playback speed control means for controlling
 the playback speed of said playback means in such
 a manner as to correspond to the checked result of
 said checking means. 40

4. An image capturing apparatus according to Claim 45
 1, wherein said network conforms with an IEEE
 1394 standard.

5. An image capturing apparatus according to Claim
 1, wherein said image capturing apparatus is a dig-
 ital video camera.

6. An image capturing apparatus according to Claim 50
 1, wherein said another electronic device is a per-
 sonal computer.

7. An image capturing method for use with an image
 capturing apparatus which can be connected to a
 network, said image capturing method comprising: 55

an image capturing step of capturing a moving

image;
 a storing step of storing said moving image cap-
 tured in said image capturing step;
 a playback step of playing back said moving im-
 age stored in said storing step;
 a maintaining step of maintaining an HTML file
 which forms a predetermined screen;
 a receiving step of receiving a command output
 by another electronic device via said network;
 a transmission step of transmitting said HTML
 file maintained in said maintaining step to said
 other electronic device via said network in such
 a manner as to correspond to said command
 received in said receiving step;
 a coding step of coding said moving image cap-
 tured in said image capturing step or said mov-
 ing image played back in said playback step by
 a predetermined method and for generating
 coded data; and
 a supplying step of supplying said coded data
 generated in said coding step to said other elec-
 tronic device via said network in such a manner
 as to correspond to said command received in
 said receiving step.

8. A recording medium having recorded therein a com-
 puter-readable program for capturing an image in a
 case where connection to a network is made, said
 program comprising:

an image capturing step of capturing a moving
 image;
 a storing step of storing said moving image cap-
 tured in said image capturing step;
 a playback step of playing back said moving im-
 age stored in said storing step;
 a maintaining step of maintaining an HTML file
 which forms a predetermined screen;
 a receiving step of receiving a command output
 by another electronic device via said network;
 a transmission step of transmitting said HTML
 file maintained in said maintaining step to said
 other electronic device via said network in such
 a manner as to correspond to said command
 received in said receiving step;
 a coding step of coding said moving image cap-
 tured in said image capturing step or said mov-
 ing image played back in said playback step by
 a predetermined method and of generating
 coded data; and
 a supplying step of supplying said coded data
 generated in said coding step to said other elec-
 tronic device via said network in such a manner
 as to correspond to said command received in
 said receiving step.

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8A




FIG. 8B






FIG. 8C





Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 130 913 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
22.10.2003 Bulletin 2003/43

(51) Int Cl.7: H04N 5/765

(43) Date of publication A2:
05.09.2001 Bulletin 2001/36

(21) Application number: 01104257.9

(22) Date of filing: 22.02.2001

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: Hata, Hajime, c/o Sony Corporation
Shinagawa-ku, Tokyo (JP)

(74) Representative: Körber, Martin, Dipl.-Phys. et al
Mitscherlich & Partner,
Patent- und Rechtsanwälte,
Postfach 33 06 09
80066 München (DE)

(30) Priority: 24.02.2000 JP 2000047558


(71) Applicant: SONY CORPORATION
Tokyo (JP)

(54) Image capturing apparatus and method, and recording medium therefor

(57) In order that a digital video (DV) camera function as a WWW server in a network, an image capturing section (11) captures an image of a subject. A DV encoder (12) encodes an image signal input from the image capturing section (11). A recording and playback section (14) plays back DV data recorded in a DV cassette tape (15). An IP packet assembling/disassembling section (19) assembles a DV signal input from the DV

encoder (12), a DV signal input from the recording and playback section (14), or an HTML file input from a WWW server processing section (21) into IP packets, and outputs them to an IEEE 1394 interface (20). The IEEE 1394 interface (20) transmits, via the network (2), the IP packets input from the IP packet assembling/disassembling section (19) to a personal computer which accessed the DV camera.

FIG. 2



EP 1 130 913 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 10 4257

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	WO 99 48276 A (FLASHPOINT TECHNOLOGY INC ; RAMIREZ MICHAEL A (US); ANDERSON ERIC C) 23 September 1999 (1999-09-23) * abstract * * page 8, line 3 - line 5 * * page 15, line 11 - line 13 * * page 16, line 16 - line 18 * * page 16, line 25 - line 27 * * page 17, line 24 - page 18, line 1 * * page 18, line 9 - line 11 * * page 20, line 18 - line 21 * * page 21, line 3 - line 4 * * page 21, line 13 - line 15 * * page 26, line 16 - line 27 * * page 27, line 14 - line 16 * * page 35; claim 1 * * page 36; claim 9 * * figure 9 *	1,4-8	H04N5/765
Y	---	2	
Y	US 5 761 438 A (SASAKI AKITOMO) 2 June 1998 (1998-06-02) * abstract * * figure 6 *	2	TECHNICAL FIELDS SEARCHED (Int.Cl.7) H04N H04L
A	US 5 715 404 A (KATSEFF HOWARD P ET AL) 3 February 1998 (1998-02-03) * column 15, line 31 - line 35 * * claim 1 * * figure 5 *	3	
A	US 5 611 038 A (SHAW STEVEN M ET AL) 11 March 1997 (1997-03-11) * abstract; figure 10 * * figure 7B *	1,3	
The present search report has been drawn up for all claims			
Place of search		Date of completion of the search	Examiner
THE HAGUE		11 August 2003	Braga, J
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03/92 (P04C01)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 10 4257

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	WO 96 02106 A (VISION 1 INT LTD ;VELLACOTT OLIVER RICHARD (GB)) 25 January 1996 (1996-01-25) * the whole document * -----	1,7,8	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 11 August 2003	Examiner: Braga, J
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03 92 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 10 4257

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

11-08-2003

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9948276	A	23-09-1999	US 6567122 B1	20-05-2003
			AU 1950799 A	11-10-1999
			DE 69906711 D1	15-05-2003
			EP 1062800 A1	27-12-2000
			JP 2002507862 T	12-03-2002
			WO 9948276 A1	23-09-1999
US 5761438	A	02-06-1998	JP 7123132 A	12-05-1995
US 5715404	A	03-02-1998	US 5822537 A	13-10-1998
			CA 2140850 A1	25-08-1995
			EP 0669587 A2	30-08-1995
US 5611038	A	11-03-1997	US 6404928 B1	11-06-2002
			US 5754766 A	19-05-1998
			US 6091857 A	18-07-2000
			US 5457780 A	10-10-1995
WO 9602106	A	25-01-1996	AU 2894295 A	09-02-1996
			WO 9602106 A1	25-01-1996
			GB 2296156 A	19-06-1996

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82